
Meridian 1

Enhanced Asynchronous Interface Line Unit

Description and formats

Document Number: 553-2731-203

Document Release: Standard 3.0

Date: December 1994

© 1990, 1994

All rights reserved

Printed in the United States of America

Information is subject to change without notice. Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

Revision history

August 10, 1990

Standard, release 1.0. Reissued for compliance with Northern Telecom standard 164.0.

August 31, 1992

Standard, release 2.0. This document was reissued to include technical content updates. Due to the extent of changes, revision bars were not used.

December 1994

Standard, release 3.0. Reissued to include editorial changes and indexing. Due to the extent of the changes, revision bars are not used.

Contents

Description	1
Related documents	3
Compatible data terminal equipment (DTE) devices	4
Physical description	5
Power requirements	9
Maintenance	9
Specifications	9
Environmental	9
Electrical	10
Timing requirements	10
Ordering information	12
Installation and testing	15
Preinstallation information	15
EAILU installation	16

List of figures

Figure 1	
EAILU application diagram	2
Figure 2	
EAILU block diagram	6
Figure 3	
Long Break generation by means of DTR drop	11
Figure 4	
DSR, DCD control by means of break detect	11
Figure 5	
EAILU connections	25

List of tables

Table 1	
EAILU DB-25 connector pin assignments	8
Table 2	
Terminals that pass the qualification test	13
Table 3	
Pair-terminations at the NT8D13 PE Module I/O Panel connectors A, C, E, and G for the AILC QPC430 (Single Loop Mode)	17
Table 4	
Pair-terminations at the NT8D13 PE Module I/O Panel connectors B, D, and F for the AILC QPC430 (Single Loop Mode)	21